

## LISTING OF CLAIMS

1. (Currently Amended) A vehicle headlight bulb comprising a lamp envelope, a light source (2) arranged inside the lamp envelope (1), and a lamp base, wherein

the lamp envelope (1) has a sealed end (11) which is essentially constructed to be cuboid formed by with two mutually opposite broad faces (110) and two mutually opposite narrow end faces (111),

the lamp base has a metallic sleeve (3) in which ~~the~~ said sealed end (11) of the lamp envelope (1) is fixed,

~~characterized in that~~ at least one of the narrow end faces (111) of the sealed end and the metallic base sleeve (3) are provided with matching means (1110, 33) for a latch connection, and

the metallic base sleeve has at least one opening in the area of the broad faces of said sealed end of the lamp envelope, wherein

the metallic base sleeve has at least two plates which are molded on to two mutually opposite edges of said opening and rest against one of said broad faces of the sealed end of the lamp envelope, and wherein

said sealed end is equipped with a molded-on pair of guide webs extending in the longitudinal direction of the lamp envelope, respectively, said guide webs serving as a stop for the free ends of said at least two plates.

2. (Currently Amended) The vehicle headlight bulb as claimed in claim 1, wherein ~~characterized in that~~ the at least one narrow end face (111) is provided with at least one notch (1110) and the metallic base sleeve (3) is equipped with a wall area (33) engaging in the former.

3. (Currently Amended) The vehicle headlight bulb as claimed in claim 2, wherein ~~characterized in that~~ the wall area (33) is at least one locking plate pointing into the inside space of the base sleeve (3).

4. (Currently Amended) The vehicle headlight bulb as claimed in claim 2, wherein ~~characterized in that~~ the wall area (33) is constructed as at least one bulge, pointing into the inside space of the base sleeve (3), in the base sleeve wall.

5. (Cancelled)

6. (Cancelled)

7. (Currently Amended) The vehicle headlight bulb as claimed in claim [[6]]1, wherein ~~characterized in that~~ the broad face (110) of the sealed end (11) of the lamp envelope (1) is provided with at least two molded-on guide webs (114, 115) extending in the longitudinal direction of the vehicle headlight bulb, which serve as a stop for in each case one of the two plates (34, 35).